



Shenzhen Office :

3-A1,Building A,Qingchuangcheng,Pinkexiao zhen,Zhangkeng community,
Minzhi Town,Longhua District,Shenzhen,Guangdong Province,China
Tel: 86.755.8886.8949

China Factory :

No.28 Binjiang Blvd., Shishuikou Village,Qiaotou Town,Dongguan,Guang Dong Province
Tel: 86.769.8929.7777

Vietnam Factory :

P-9, Trang Due Industrial Zone Belongs To Dinh Vu - Cat Hai Economic Zone, An Hoa
Commune,An Duong District, Hai Phong City
Tel: 84.225.3558.880

Web: www.power7tech.com

Power Products





Dongguan Factory



Vietnam Factory

– COMPANY PROFILE

Power 7 Technology specializes in the innovative design and manufacturing of complex external storage solutions, mobile power devices, and peripheral solutions that are compatible with variety of computer and mobile iOS platforms. Our dedication to excellence in technology, innovation, design, quality, and customer service has led to our reputation on a global scale. We have over 30 years of OEM/ODM and Electronics Manufacturing Services (EMS) experience. As a trusted supplier and manufacturer, we created long-term partnerships with several world-class and local businesses that rely on our knowledge, expertise, and services.

– COMPANY VISION

To design, manufacture, and deliver excellent products and solutions to our customers in a timely and superior manner. Accept projects that are within our skills, knowledge, expertise and focus on the ones in which we excel in to become the partner of choice.

– COMPANY PHILOSOPHY

Competitive Advantage: Competitive advantages are established through significant investments in research and development. Three principles guide our engineering and production practices: QUALITY, QUALITY, and QUALITY. Quality serves as our strongest competitive advantage. Creative Innovation: Knowledge, experience, and imagination work together to foster creativity in the development of featured products.

Accountability Commitment: Providing steadfast support for our products and services is at the core of our meticulous approach.



A11-30W with Power Bank

- Battery Capacity: 10,000mAh, 21700-5000mAh*2
- GaN(Gallium nitride) technology inside
- Input: AC 100-240V
USB-C1: 5V/3A, 9V/3A,15V/2A
- Output: AC Mode: USB-C1: PD 30W,
5V/3A, 9V/3A,15V/2A,20V/1.5A USB-C2: PD 30W
Power bank Mode: USB-C1: PD 30W,
5V/3A, 9V/3A,15V/2A,20V/1.5A USB-C2: PD 30W
- Case material: Plastic
- Dimension: 108mm X51.5mm X31mm





C26 Magnetic Wireless Power Bank

- Battery Capacity: 10,000mAh, Li-Polymer
- Number of Battery Cell: 2
- Input: USB-C: PD 18W
- Output: USB-C: PD 20W
USB-A: QC 18W
Magnetic Wireless: 5W, 7.5W, 15W
iWatch Wireless: 5W
Total 20W Maximum Output
- Material: Plastic
- Dimensions: 107mm X 68mm X 23.5mm





A05 20W Wall Charger

- Input: AC 100V-220V, 50/60Hz
- Output: USB-C: 5V/3A, 9V/2.22A, 12V/1.66A
Supports PPS
Total 20W Maximum Output
- Material: Plastic
- Dimensions: 30mm X 30mm X 31mm

A09 30W Wall Charger

- Input: AC 100V-220V, 50/60Hz
- Output: USB-C: 5V/3A, 9V/3A, 15V/2A, 20V/1.5A
Supports PPS
Total 30W Maximum Output
- Material: Plastic
- Dimensions: 30mm X 30mm X 31mm



A17

- Battery Capacity: 10,000mAh, 21700-5000mAh*2
- AC Input: 100-240V- 50-60Hz, 2A
- USB-C port/cable input: 5V/3A, 9V/3A, 15V/2A
- Output: Charger mode & Battery mode
- USB-C port/USB-C cable: 5V/3A, 9V/3A, 12V/2.5A, 15V/2A, 20V/1.5A
- Total output: 5V/3A
- Dimensions: 114mm X 52mm X 32mm



A10 65W

- Remark: GaN(Gallium nitride) technology inside
- Input: AC 100-240V 50/60Hz
- Output: USB-C1/C2: 65W Max
5V/3A, 9V/3A, 12V/3A,15V/3A,20V/3.25A
USB-A: 5V/3A,9V/2A,12V/1.5A 18W Max
Total Output: USB-C1+(USB-C2+A):45W+15W 60W Max
- Case material: Plastic
- Dimension: 68mm X32mm X39mm



A21 45W with Power Bank

- Battery Capacity: 10,000mAh, 955465-5000mAhx2,Li-Polymer
- Remark: GaN(Gallium nitride) technology inside
- Input: AC 100-240V 50/60Hz
USB-C1/Cable: 5V/3A, 9V/3A,15V/2A PD 30W
- Output: AC Mode: USB-C1/Type-C Cable: PD 45W,
5V/3A,9V/3A,12V/3A,15V/3A,20V/2.25A
Total Output: 5V/4.8A Max
Power bank Mode:
USB-C1 / Type-C Cable: PD 40W,
5V/3A, 9V/3A, 12V/3A, 15V/2.66A, 20V/2A
Total Output: 5V/4.8A Max
- Case material: Plastic
- Dimension: 112mm X63.5mm X38.5mm



A20 20W with Power Bank

- Remark: GaN(Gallium nitride) technology inside 21700-5000mAh*1
- Input: AC 100-240V 50/60Hz
USB-C Cable: 5V/3A, 9V/2.22A PD 20W
- Output: AC Mode: USB-C: PD18W 5V/3A,9V/2A,12V/1.5A
USB-C Cable: PD 20W 5V/3A,9V/2.22A,12V/1.67A
Share: 5V/3A
Power bank Mode:
USB-C: PD18W 5V/3A, 9V/2A, 12V/1.5A
USB-C Cable: PD 20W 5V/3A, 9V/2.22A, 12V/1.67A
Share: 5V/3A
- Case material: Plastic
- Dimension: 114mm X41mm X27mm



B19 30W

- Battery Capacity: 705880-5000mAh*2
Semi Solid State Battery
- Input: USB-C: 5V/3A,9V/3A,12V/2.5A,15V/2A PD 30W Max
- Output: USB-C: 5V/3A,9V/3A,12V/2.5A,15V/2A,20V/1.5A
PD 30W Max
USB-A: 5V/3A,9V/2A,12V/1.5A QC 18W
- Case material: Plastic
- Dimension: 119.5mm X69mm X19.1mm



B23

- Battery capacity: 676076 5000mAh*2
- Input: USB-C1/C-cable 5V/3A,9V/3,12V/2.5A (30W Max)
- Output: USB-C1/C-cable: PD 5V/3A,9V/3A,12V/3A,15V2.67A,20V2A (40W MAX)
USB-A: 5/3A, 9V/2A, 12V/1.5A
USB-C1/C-cable+USB A total share: 5V/3A, 9/3A(PD27W)+5V/2.4A 12W
USB-C1+USB-C cable: 5V/3A,9/3A(PD27W)+5V/2.4A 12W
Total Output: USB-C cable 5V/3A, 9V/2.2A(PD 20W),
USB-C Port+USB-A Port 5V3A
- Material: Plastic
- Dimension: 108mm X68.6mm X29.5mm



B22

- Battery capacity: 21700 5000mAh*2
- Input: 5V/3A 9V/3A 12V/2.5A PD30W
- Output: USB-C1/C-cable: 5V/3A, 9V/3A, 12V/3.33A, 15V/2.67A, 20V/2A
USB-A Output: 5/3A, 9V/2A, 12V/1.5A
USB-C1/C-cable + USB A total share:
5V/3A, 9/3A(PD27W)+5V/2.4A 12W
USB-C1+USB-C cable: 5V/3A,9/3A(PD27W)+5V/2.4A 12W
Total Output: USB-C cable 5V/3A, 9V/2.2A(PD 20W),
USB-C1+USB-A 5V3A
- Material: Plastic
- Dimension: 85mm X51.5mm X38mm



B02

- Battery Capacity: 10,000mAh, 21700 5000mAh*2
- Input: USB-C 5V3A/9V3A/12V2.5A
- Output: USB-A: 5V/3A, 9V/2A, 12V/1.5A
USB-C: 5V/3A, 9V/3A,
12V/2.5A, 15V/2A
- Total: USB-A+USB-C shared 5V4.8A
- Dimension: 82mm X61mm X26mm



B12 PD35W

- Battery Capacity: 10,000mAh, 21700 5000mAh*2
- Input: USB-C1: 5V/3A,9V/3A,12V/2.91A,15V/2.33A PD 35W
USB-Cable: 5V/3A,9V/3A,12V/2.91A,15V/2.33A PD 35W
- Output: USB-C: 5V/3A,9V/3A,12V/2.91A,15V/2.33A PD 35W Max
USB-Cable: 5V/3A,9V/3A,12V/2.91A,15V/2.33A PD 35W
Max Both USB-Cable & USB-C: Share 5V/4.8A
- Case material: Plastic
- Dimension: 85mm X63mm X26mm



B17

- Battery 21700-5000*4 20,000mAh
- Input: USB-C: PD 65W Max
- Output: USB-C1: 5V/3A,9V/3A,12V/2.5A PD 30W Max
USB-C2: 5V/3A,9V/3A,12V/3A ,15V/3A,20V/5A
PD 100W Max
USB-A: 5V/3A,9V/2A,12V/1.5A,10V/2.25A,QC 22.5W
- Case material: Plastic
- Dimension: 140mm X81mm X26.5mm



B05B

- Battery Capacity: 21700, 5000mAh*2
- Input: USBC 5V/3A, 9V/2.2A, 12V/1.6A
- Output: USBC 5V/3A, 9V/2.2A, 12V/1.6A
USBA 5V/3A, 9V/2A, 12V/1.5A
- Total: USBA+USBC shared 5V/3A
- Dimension: 78mm X58mm X25mm

B13 PD20W

- Battery Capacity: 5,000mAh, 21700 5000mAh*1
- Input: USB-C1/C2: 5V/3A,9V/2A PD 18W
- Output: USB-C1/C2: 5V/3A,9V/2.22A,12V/1.67A
PD 20W Max
- Case material: Plastic
- Dimension: 78mm X36.5mm X26mm



B15

- Battery Capacity: 21700 5000mAh*5
- Input: USB-C2: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A 65W Max
- Output: USB-C1: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A, 28V/5A 140W Max
USB-C2: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A
USB-A: 5V/4.5A, 9V/2A, 12V/2A, 10V/2.25A
- Total Output: C1+C2 150W Max
- Dimension: 160mm X81mm X26.5mm



B16

- Battery Capacity: 5000mAh*2
Semi Solid State Battery
- Input: USB-C: 5V/3A, 9V/2.22A PD20W
- Output: USB-C: 5V/3A, 9V/2.22A, 12V/1.67A PD20W
USB-A: 5V/3A, 9V/2A, 12V/1.5A
- Total: USB-A+USBC shared 5V/3A
- Dimension: 117mm X69mm X18.5mm





B03 PD20W

- Battery Capacity: 5,000mAh, 21700 5000mAh*1
- Input: 5V/3A,9V/2.2A,12V/1.6A PD 20W Max
- Output: USB-C: 5V/3A,9V/2.2A,12V/1.6A PD 20W Max
USB-A: 5V/3A,9V/2A,12V/1.5A QC 18W Max
Both USB-A & USB-C: 5V/3A 15W(Max)
- Case material: Plastic
- Dimension: 78mm X 39mm X 25mm

B06 Power Bank

- Battery Capacity: 20,000mAh, 21700 5,000mAh*4
- Input: USB-C: 5V/3A, 9V/3A, 12V/2.5A, 15V/2A, 20V/1.5A PD 30W Max
- Output: USB-C: 5V/3A, 9V/3A, 12V/3A,15V/3A, 20V/3A PD 60W Max
USB-A: 5V/3A, 9V/2A, 12V/1.5A 18W Max
- Material: Plastic
- Dimensions: 149mm X 58mm X 25mm



C06 Wireless Charger

- Input: USB-C PD 18W
- Output: Wireless: 5W, 7.5W, 10W
- Material: Plastic and PU
- Dimensions: 90mm X 7.3mm

C30 Magnetic Wireless Car Mount

- Input: USB-C: PD 20W
- Output: Wireless: 5W, 7.5W, 10W
Total 15W Maximum Output
- Material: Plastic and PU
- Dimensions: 84mm X 64mm X 10mm (Body Only)



C28

- Battery Capacity: 10000mAh Lithium-ion Polymer Battery
- Input: USB-C: 5V/3A,9V/2.22A 12V/1.67A PD 20W Max
- Output: USB-C: 5V/3A,9V/3A,12V/2.25A PD 27W Max
Wireless: BPP 5W,Apple 7.5W,MPP 15W,25W
- Case material: Plastic
- Dimension: 108.5mm X70mm X17.5mm



C27

- Battery capacity: 506578-5000mAh*1
- Input: PD 5V/3A,9V/2.22A, 20W Max
- Output: USB-C PD 5V/3A,9V/3A,12V/2.5A(30W Max)
Wireless output: 25w Max
Total share 5V/3A
- Material: Plastic
- Dimension: 100.8mm X69.8mm X8.3mm



C17

- Input: 5V/9V/12V/15V PD
- Output: 5W, 7.5W, 15W, 25W
- Output: AL and Plastic
- Output: 59mm X7.7mm



C25

- Remark: Magnetic Wireless Charger with PB
- Battery Capacity: 5,000mAh Semi Solid State Battery
 - Support MPP 15W
 - C25 without stand
 - C25L with Stand
- Input: PB mode: USB-C: PD 5V/2A
Pass-through mode: USB-C PD 20W
- Output: PB mode: USB-C: PD 20W
Wireless: BPP 5W, Apple 7.5W, MPP 15W
- Case material: Plastic
- Dimension: 105mm X69mm X12.5mm



S43CC- 45W

- Remark: US, JP, EU, UK Plug Available
- Input: AC 100V-240V,50/60Hz, 1A
- Output: Type-C1: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/2.25A
Type-C2: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/2.25A
- Share: Type-C1 PD30W+Type-C2 12W
- Material & Finish: Plastic, Texture
- Dimension: 14.5*43.5*76 mm



S63C - 65W

- Remark: US, JP, EU, UK Plug Available
- Input: AC 100V-240V,50/60Hz, 1.3A
- Output: Type-C1: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A
PPS:5V-20V/3A
- Material & Finish: Plastic, Texture
- Dimension: 34*37.5*64.5 mm(Not include Plug)



S63CA - 65W

- Remark: US, JP, EU, UK Plug Available
- Input: AC 100V-240V,50/60Hz, 1.3A
- Output: Type-C1: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A
USB-A1: 5V/3A, 9V/2A, 12V/2.25A, 20V/1.35A
Share: Type-C1 PD45W+ USB-A 12W
- Material & Finish: Plastic, Texture
- Dimension: 34*37.5*64.5 mm(Not include Plug)



S63CC - 65W

- Remark: US, JP, EU, UK Plug Available
- Input: AC 100V-240V,50/60Hz, 1.3A
- Output: Type-C1: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A
Type-C2: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A
Share: Type-C1 PD45W+Type-C2 12W
- Material & Finish: Plastic, Texture
- Dimension: 34*37.5*64.5 mm(Not include Plug)



S63CCA - 65W

- Remark: US, JP, EU, UK Plug Available
- Input: AC 100V-240V,50/60Hz, 1.3A
- Output: Type-C1: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A
Type-C2: 5V/3A, 9V/3A, 12V/2.25A, 20V/1.35A
USB-A: 5V/3A, 9V/3A, 12V/2.25A, 20V/1.35A
Share: Type-C1 PD45W+(Type-C2+USB-A) 12W
- Material & Finish: Plastic, Texture
- Dimension: 34*37.5*64.5 mm(Not include Plug)



S64CCA - 65W

- Remark: US, JP, EU, UK Plug Available
- Input: AC 100V-240V,50/60Hz, 1.3A
- Output: USB-C1: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A
USB-C2: 5V/3A, 9V/3A, 12V/2.25A, 20V/1.35A
USB-A: 5V/3A, 9V/3A, 12V/2.25A, 20V/1.35A
Share: USB-C1 PD45W + (USB-C2 + USB-A) 12W
- Material & Finish: Plastic, Texture
- Dimension: 34*37.5*71.6 mm(Not include Plug)





T01 - 100W

- Remark: Modified Sine Wave for AC output 110V/220V available Capacity: 27000mAh 6*21700-4500mAh
- Input: USB-C: 5V/3A,9V/3A,12V/3A,15V/3A,20V/3A
- Output: USB-C: 5V/3A,9V/3A,12V/3A,15V/3A,20V/3A
USB-A: SCP10V/2.25A,5V/3A,9V/2.0A,12V/1.5A
AC: 220V±3% 50Hz or 110V±3% 60Hz 100W
- Material & Finish: Plastic, Texture
- Dimension: 193*62*85mm/ About 1KG

T02 - 200W

- Remark: Modified Sine Wave for AC output 110V/220V available Capacity: 54000mAh 12*21700-4500mAh
- Input: USB-C: 5V/3A,9V/3A,12V/3A,15V/3A,20V/3A
- Output: USB-C: 5V/3A,9V/3A,12V/3A,15V/3A,20V/3A
USB-A: SCP10V/2.25A,5V/3A,9V/2.0A,12V/1.5A
AC: 220V±3% 50Hz or 110V±3% 60Hz 200W
- Material & Finish: Plastic, Texture
- Dimension: 217*83*90mm/ About 1.8KG



S65 -CCA 65W

- Input: AC 100V-240V,50/60Hz
- Output: USB-C1: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A
USB-C2: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A
USB-A: 5V/3A, 9V/2A, 12V/1.5A
Share: USB-C1 PD45W+(USB-C2+USB-A) 15W
- Material: Plastic, Texture
- Remark: US, JP, EU, UK Plug Available





S31 - 35W

- Input: AC 100V-240V,50/60Hz
- Output: USB-C: 5V/3A, 9V/3A, 12V/2.9A, 15V/2.3A, 20V/1.75A
USB-A: 5V/3A, 9V/3A, 12V/2.5A
Share: USB-C+USB-A 5V/3A 15W
- Material: Plastic, Texture
- Remark: US, JP, EU, UK Plug Available

S41 - 45W

- Input: AC 100V-240V,50/60Hz
- Output: USB-C1: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/2.25A
USB-C2: 5V/3A, 9V/2A, 12V/3A, 15V/3A, 20V/2.25A
Share: USB-C Cable 20W+USB-C2 20W
- Material: Plastic, Texture
- Remark: US, JP, EU, UK Plug Available



S61 - 65W

- Input: AC 100V-240V,50/60Hz
- Output: USB-C1: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A
USB-C2: 5V/3A, 9V/3A, 12V/2.5A, 15V/2A, 20V/1.5A
USB-A: 5V/3A, 9V/2A, 12V/2.5A, 20V/1.5A
Share: USB-C1 PD45W+(USB-C2+USB-A)15W
- Material: Plastic, Texture
- Remark: US, JP, EU, UK Plug Available





S32 - CA 35W

- Input: AC 100V-240V,50/60Hz
- Output: USB-C: 5V/3A, 9V/3A, 12V/2.9A, 15V/2.3A, 20V/1.75A 35W Max
USB-A: 5V/3A, 9V/2A, 12V/1.5A
Share: USB-C+USB-A 5V/3A
- Material: Plastic, Texture
- Remark: US, JP, EU, UK Plug Available



S42 - CC 45W

- Input: AC 100V-240V,50/60Hz
- Output: USB-C1: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/2.25A
USB-C2: 5V/3A, 9V/2A, 12V/3A, 15V/3A, 20V/2.25A
Share: USB-C1 20W+USB-C2 20W
- Material: Plastic, Texture
- Remark: US, JP, EU, UK Plug Available



S62 - CC 65W

- Input: AC 100V-240V,50/60Hz
- Output: USB-C1: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A
USB-C2: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A
Share: USB-C1 45W+USB-C2 20W
- Material: Plastic, Texture
- Remark: US, JP, EU, UK Plug Available

S60 - 65W

- Input: AC 100V-240V,50/60Hz
- Output: USB-C Cable: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A
USB-C2: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A
Share: USB-C Cable 45W+USB-C2 20W
- Material: Plastic, Texture
- Dimension: 60mm X61.85mm X30mm
- Remark: US, JP, EU, UK Plug Available



S80

- Input: AC 100V-240V,50/60Hz
- Output: USB-C1: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A
USB-C2: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A
USB-C3: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A
USB-A1: 5V/3A, 9V/2A, 12V/1.5A
Share: C1+C2+C3+A1: 45W+35W+7.5W+7.5W
AC Sockets: 10A/110V/1100W
- Material: Plastic, Texture
- Dimension: 93mm X93mm X28.1mm (Not include cable)
- Remark: US, JP, EU, UK Plug Available



S81

- Input: AC 100V-240V,50/60Hz
- Output: USB-C cable: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A
USB-C2: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A
USB-C3: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A
USB-A1: 5V/3A, 9V/2A, 12V/1.5A
Share: C1+C2+C3+A1: 45W+35W+7.5W+7.5W
- Material: Plastic, Texture
- Dimension: 93mm X93mm X28.1mm (Not include cable)
- Remark: US, JP, EU, UK Plug Available



W01

- Input: USB-C: 9V/3A,12V/3A
- Output: Wireless: 5W/7.5W/10W/15W/25W
- Material: Plastic
- Dimension: 64mm X49mm
- Remark: Qi 2.2 25W



W02

- Input: USB-C: 9V/2A
- Output: Wireless: 5W/7.5W/10W/15W
- Material: AL + Glass
- Remark: No Qi Certification
- Dimension: 64.1mm X99mm X25.7mm

W03

- Input: USB-C: 9V/2A
- Output: Wireless: 5W/7.5W/10W/15W
- Material: AL + Glass
- Remark: No Qi Certification
- Dimension: 87mm X60mm X6.5mm





S20 - 20W

- Input: AC 100V-240V,50/60Hz
- Output: USB-C: 5V3A,9V2.22A,12V1.67A 20W(Max)
USB-Cable: 5V3A,9V2.22A,12V1.67A 20W(Max)
Share: USB-Cable + USB-C 5V/3A 15W(Max)
- Material: Plastic,Texture
- Dimension: 97.5mm X50.9mm X29.8mm
- Remark: US, JP, EU, UK Plug Available

S30 - 30W

- Input: AC 100V-240V,50/60Hz
- Output: USB-C: 5V/3A,9V/3A,12V/2.5A,
15V/2A,20V/1.5A 30W(Max)
USB-Cable: 5V/3A, 9V/3A, 12V/2.5A,
15V/2A, 20V/1.5A 30W(Max)
Share: USB-Cable + USB-C 5V/3A 15W(Max)
- Material: Plastic, Texture
- Dimension: 61.5mm X50.8mm X30mm
- Remark: US, JP, EU, UK Plug Available



S62F-CCA 65W

- Input: AC 100V-240V,50/60Hz
- Output: USB-C1: 5V/3A,9V/3A,12V/3A,15V/3A,
20V/3.25A 65W(Max)
USB-C2: 5V/3A,9V/3A,12V/3A,15V/3A,
20V/3.25A 65W(Max)
USB-A: 5V3A,9V2A,12V1.5A 18W(Max)
Share: USB-C1 45W + (USB-C2+A) 15W 60W(Max)
- Material & Finish: Plastic,Texture
- Dimension: 50mm X30mm X53.5mm
- Remark: US,JP,EU,UK Plug Available



Y01

- Remark: Battery Capacity: 12000mAh(Lithium polymer battery)
Start current: 400A-500A
Peak current: 800A-1000A
Inflation pressure: 3-140psi
Inflation flow rate: 22L/min
Inflation rate: 195/65/R15 tire 0-36psi 5'±5s
- Input: TYPE-C: 5V/3A,9V/3A,12V/2.5A PD 30W
- Output: TYPE-C: 5V/3A,9V/3A,12V/2.5A
PD 30W USB max 5V/2A
- Material: Plastic
- Dimension: 208mm X92mm X94mm



Y02

- (Lithium polymer battery)
- Remark: Battery Capacity: 10000mAh
Start current: 400A-500A
Peak current: 800A-1000A
Inflation pressure: 3-140psi
Inflation flow rate: 22L/min
Inflation rate: 195/65/R15 tire 0-36psi 5'±5s
- Input: TYPE-C: 5V/2A,9V/2A
- Output: TYPE-C: 5V/2A
- Material: Plastic
- Dimension: 212mm X107mm X56mm



Y03

- (Lithium polymer battery)
- Remark: Battery Capacity: 8000mAh
Start current: 300A
Peak current: 500A
- Input: TYPE-C: 5V
- Output: USB: 5V/2A,5V/1A
- Material: Plastic
- Dimension: 187mm X87mm X40mm

