POWER 7 TECHNOLOGY

Shenzhen Office :
3-A1,Building A,Qingchuangcheng,Pinkexiao zhen,Zhangkeng community,
Minzhi Town,Longhua District,Shenzhen,Guangdong Province,China
Tel: 86.755.8886.8949

China Factory :
No.28 Binjiang Blvd., Shishuikou Village,Qiaotou Town,Dongguan,Guang Dong Province
Tel: 86.769.8929.7777

Vietnam Factory :
P-9, Trang Due Industrial Zone Belongs To Dinh Vu - Cat Hai Economic Zone, An Hoa
Commune,An Duong District, Hai Phong City
Tel: 84.225.3558.880

Web: www.power7tech.com

Power Products

POWER 7 TECHNOLOGY
泰克威云储科技

BSCI ISO14001 ISO9001 Global Recycled Standard Responsible Business Alliance

Dongguan Factory

Vietnam Factory

– COMPANY PROFILE

Power 7 Technology specializes in the innovative design and manufacturing of complex external storage solutions, mobile power devices, and peripheral solutions that are compatible with variety of computer and mobile iOS platforms. Our dedication to excellence in technology, innovation, design, quality, and customer service has led to our reputation on a global scale. We have over 30 years of OEM/ODM and Electronics Manufacturing Services (EMS) experience. As a trusted supplier and manufacturer, we created long-term partnerships with several world-class and local businesses that rely on our knowledge, expertise, and services.

– COMPANY VISION

To design, manufacture, and deliver excellent products and solutions to our customers in a timely and superior manner. Accept projects that are within our skills, knowledge, expertise and focus on the ones in which we excel in to become the partner of choice.

– COMPANY PHILOSOPHY

Competitive Advantage: Competitive advantages are established through significant investments in research and development. Three principles guide our engineering and production practices: QUALITY, QUALITY, and QUALITY. Quality serves as our strongest competitive advantage.
Creative Innovation: Knowledge, experience, and imagination work together to foster creativity in the development of featured products.
Accountability Commitment: Providing steadfast support for our products and services is at the core of our meticulous approach.

A11-30W with Power Bank

- Battery Capacity: 10,000mAh, 21700-5000mAh*2
- GaN(Gallium nitride) technology inside
- Input: AC 100-240V
  USB-C1: 5V/3A, 9V/3A,15V/2A
- Output: AC Mode: USB-C1: PD 30W,
  5V/3A, 9V/3A,15V/2A,20V/1.5A USB-C2: PD 30W
  Power bank Mode: USB-C1: PD 30W,
  5V/3A, 9V/3A,15V/2A,20V/1.5A USB-C2: PD 30W
- Case material: Plastic
- Dimension: 108mm X51.5mm X31mm

C26 Magnetic Wireless Power Bank

- Battery Capacity: 10,000mAh, Li-Polymer
- Number of Battery Cell: 2
- Input: USB-C: PD 18W
- Output: USB-C: PD 20W
  USB-A: QC 18W
  Magnetic Wireless: 5W, 7.5W, 15W
  iWatch Wireless: 5W
  Total 20W Maximum Output
- Material: Plastic
- Dimensions: 107mm X 68mm X 23.5mm

A05 20W Wall Charger

- Input: AC 100V~220V, 50/60Hz
- Output: USB-C: 5V/3A, 9V/2.22A, 12V/1.66A
  Supports PPS
  Total 20W Maximum Output
- Material: Plastic
- Dimensions: 30mm X 30mm X 31mm

A09 30W Wall Charger

- Input: AC 100V~220V, 50/60Hz
- Output: USB-C: 5V/3A, 9V/3A, 15V/2A, 20V/1.5A
  Supports PPS
  Total 30W Maximum Output
- Material: Plastic
- Dimensions: 30mm X 30mm X 31mm

A17

- Battery Capacity: 10,000mAh, 21700-5000mAh*2
- AC Input: 100-240V~ 50-60Hz,2A
- USB-C port/cable input: 5V/3A, 9V/3A, 15V/2A
- Output: Charger mode & Battery mode
- USB-C port/USB-C cable: 5V/3A, 9V/3A, 12V/2.5A, 15V/2A, 20V/1.5A
- Total output: 5V/3A
- Dimensions: 114mm X 52mm X 32mm

A10 65W

- Remark: GaN(Gallium nitride) technology inside
- Input: AC 100-240V 50/60Hz
- Output: USB-C1/C2: 65W Max
  5V/3A, 9V/3A, 12V/3A,15V/3A,20V/3.25A
  USB-A: 5V/3A,9V/2A,12V/1.5A 18W Max
  Total Output: USB-C1+(USB-C2+A):45W+15W 60W Max
- Case material: Plastic
- Dimension: 68mm X32mm X39mm

A21 45W with Power Bank

- Battery Capacity: 10,000mAh, 124652-5000mAhx2,Li-Polymer
- Remark: GaN(Gallium nitride) technology inside
- Input: AC 100-240V 50/60Hz 2A,
  USB-C1/Cable: 5V/3A, 9V/3A,15V/2A PD 30W
- Output: AC Mode: USB-C1/Type-C Cable: PD 45W,
  5V/3A,9V/3A,12V/3A,15V/3A,20V/2.25A
  Total Output: 5V/4.8A Max
  Power bank Mode:
  USB-C1 / Type-C Cable: PD 40W,
  5V/3A, 9V/3A, 12V/3A, 15V/2.66A, 20V/2A
  Total Output: 5V/4.8A Max
- Case material: Plastic
- Dimension: 102mm X56.4mm X47.8mm

A20 20W with Power Bank

- Remark: GaN(Gallium nitride) technology inside 21700-5000mAh*1
- Input: AC 100-240V 50/60Hz
  USB-C Cable: 5V/3A, 9V/2.22A PD 20W
- Output: AC Mode: USB-C: PD18W 5V/3A,9V/2A,12V/1.5A
  USB-C Cable: PD 20W 5V/3A,9V/2.22A,12V/1.67A
  Share: 5V/3A
  Power bank Mode:
  USB-C: PD18W 5V/3A, 9V/2A, 12V/1.5A
  USB-C Cable: PD 20W 5V/3A, 9V/2.22A, 12V/1.67A
  Share: 5V/3A
- Case material: Plastic
- Dimension: 114mm X41mm X27mm

B19 30W

- Battery Capacity: 705880-5000mAh*2
  Semi Solid State Battery
- Input: USB-C: 5V/3A,9V/3A,12V/2.5A,15V/2A PD 30W Max
- Output: USB-C: 5V/3A,9V/3A,12V/2.5A,15V/2A,20V/1.5A
  PD 30W Max
  USB-A: 5V/3A,9V/2A,12V/1.5A QC 18W
- Case material: Plastic
- Dimension: 119.5mm X69mm X19.1mm

B23

- Battery capacity: 676076 5000mAh*2
- Input: USB-C1/C-cable 5V/3A,9V/3,12V/2.5A (30W Max)
- Output: USB-C1/C-cable: PD 5V/3A,9V/3A,12V/3A,15V2.67A,20V2A (40W MAX)
  USB-A: 5/3A, 9V/2A, 12V/1.5A
  USB-C1/C-cable+USB A total share: 5V/3A, 9/3A(PD27W)+5V/2.4A 12W
  USB-C1+USB-C cable: 5V/3A,9/3A(PD27W)+5V/2.4A 12W
  Total Output: USB-C cable 5V/3A, 9V/2.2A(PD 20W),
  USB-C Port+USB-A Port 5V3A
- Material: Plastic
- Dimension: 108mm X68.6mm X29.5mm

B22

- Battery capacity: 21700 5000mAh*2
- Input: 5V/3A 9V/3A 12V/2.5A PD30W
- Output: USB-C1/C-cable: 5V/3A, 9V/3A, 12V/3.33A, 15V/2.67A, 20V/2A
  USB-A Output: 5/3A, 9V/2A, 12V/1.5A
  USB-C1/C-cable + USB A total share:
  5V/3A, 9/3A(PD27W)+5V/2.4A 12W
  USB-C1+USB-C cable: 5V/3A,9/3A(PD27W)+5V/2.4A 12W
  Total Output: USB-C cable 5V/3A, 9V/2.2A(PD 20W),
  USB-C1+USB-A 5V3A
- Material: Plastic
- Dimension: 85mm X51.5mm X38mm

B02

- Battery Capacity: 10,000mAh, 21700 5000mAh*2
- Input: USB-C 5V3A/9V3A/12V2.5A
- Output: USB-A: 5V/3A, 9V/2A, 12V/1.5A
  USB-C: 5V/3A, 9V/3A,
  12V/2.5A, 15V/2A
- Total: USB-A+USB-C shared 5V4.8A
- Dimension: 82mm X61mm X26mm

B12 PD35W

- Battery Capacity: 10,000mAh, 21700 5000mAh*2
- Input: USB-C1: 5V/3A,9V/3A,12V/2.91A,15V/2.33A PD 35W
  USB-Cable: 5V/3A,9V/3A,12V/2.91A,15V/2.33A PD 35W
- Output: USB-C: 5V/3A,9V/3A,12V/2.91A,15V/2.33A PD 35W Max
  USB-Cable: 5V/3A,9V/3A,12V/2.91A,15V/2.33A PD 35W
  Max Both USB-Cable & USB-C: Share 5V/4.8A
- Case material: Plastic
- Dimension: 85mm X63mm X26mm

B17

- Battery 21700-5000*4 20,000mAh
- Input: USB-C: PD 65W Max
- Output: USB-C1: 5V/3A,9V/3A,12V/2.5A PD 30W Max
  USB-C2: 5V/3A,9V/3A,12V/3A ,15V/3A,20V/5A
  PD 100W Max
  USB-A: 5V/3A,9V/2A,12V/1.5A,10V/2.25A,QC 22.5W
- Case material: Plastic
- Dimension: 140mm X81mm X26.5mm

B05B

- Battery Capacity: 21700, 5000mAh*2
- Input: USBC 5V/3A, 9V/2.2A, 12V/1.6A
- Output: USBC 5V/3A, 9V/2.2A, 12V/1.6A
  USBA 5V/3A, 9V/2A, 12V/1.5A
- Total: USBA+USBC shared 5V/3A
- Dimension: 78mm X58mm X25mm

B13 PD20W

- Battery Capacity: 5,000mAh, 21700 5000mAh*1
- Input: USB-C1/C2: 5V/3A,9V/2A PD 18W
- Output: USB-C1/C2: 5V/3A,9V/2.22A,12V/1.67A
  PD 20W Max
- Case material: Plastic
- Dimension: 78mm X36.5mm X26mm

B15

- Battery Capacity: 21700 5000mAh*5
- Input: USB-C2: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A 65W Max
- Output: USB-C1: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A, 28V/5A 140W Max
  USB-C2: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A
  USB-A: 5V/4.5A, 9V/2A, 12V/2A,10v/2.25A
- Total Output: C1+C2 150W Max
- Dimension: 160mm X81mm X26.5mm

B16

- Battery Capacity: 5000mAh*2
  Semi Solid State Battery
- Input: USB-C: 5V/3A, 9V/2.22A PD20W
- Output: USB-C: 5V/3A, 9V/2.22A, 12V/1.67A PD20W
  USB-A: 5V/3A, 9V/2A, 12V/1.5A
- Total: USBA+USBC shared 5V/3A
- Dimension: 117mm X69mm X18.5mm

B24

- Battery capacity: 126280-10000mAh * 2
- Input: USB-C & USB-Cable:5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V2.25A 45W Max
- Output: USB-C & USB-Cable & USBA
  USB-C: (5-11V)/3A, 5V/3A, 9V/3A, 12V/3A, 15V3A, 20V2.25A 45W Max
  USB-Cable: (5-11V)/3A, 5V/3A, 9V/3A, 12V/3A, 15V3A, 20V2.25A 45W Max
  USBA: 5V/3A, 9V/2A, 12V/1.5A 18W Max
- Material: Plastic
- Dimension: 32.5mm X71mm X116mm

B27

- Battery capacity: 126280-10000mAh * 2
- Input: USB-C & USB-Cable: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V2.25A 45W Max
- Output: USB-C & USB-Cable & USBA
  USB-C:(5-11V)/3A, 5V/3A, 9V/3A, 12V/3A, 15V3A, 20V2.25A 45W Max
  USB-Cable: (5-11V)/3A, 5V/3A, 9V/3A, 12V/3A, 15V3A, 20V2.25A 45W Max
  USBA: 5V/3A, 9V/2A, 12V/1.5A 18W Max
- Material: Plastic
- Dimension: 31mm X72mm X113.6mm

B25 10K

- Battery capacity: 26700-5000mAh*2
- Input: USB-C: 5V/3A, 9V/3A, 12V/2.5A,
  15V/2A, 20V1.5A 30W Max
- Output: USB-C1 & USBA & USB-C2
  USB-C1:
  PD45W(5V3A, 9V3A, 12V3A, 15V3A, 20V2.25A)
  USB-C2:
  PD45W(5V3A,9V3A, 12V3A, 15V3A, 20V2.25A)
  USBA: 18W(5V3A, 9V2A, 12V1.5A)
- Material: Plastic
- Dimension: 31mm X60mm X95mm

B25 20K

- Battery capacity:26750-10000mAh*2
- Input: USB-C: 5V/3A, 9V/3A, 12V/2.5A,
  15V/2A, 20V1.5A 30W Max
- Output: USB-C1 & USBA & USB-C2
  USB-C1:
  PD45W(5V3A,9V3A,12V3A,15V3A,20V2.25A)
  USB-C2:
  PD45W(5V3A,9V3A,12V3A,15V3A,20V2.25A)
  USBA: 18W(5V3A,9V2A,12V1.5A)
- Material: Plastic
- Dimension: 31mm X60mm X95mm

B03 PD20W

- Battery Capacity: 5,000mAh, 21700 5000mAh*1
- Input: 5V/3A,9V/2.2A,12V/1.6A PD 20W Max
- Output: USB-C: 5V/3A,9V/2.2A,12V/1.6A PD 20W Max
  USB-A: 5V/3A,9V/2A,12V/1.5A QC 18W Max
  Both USB-A & USB-C: 5V/3A 15W(Max)
- Case material: Plastic
- Dimension: 78mm X 39mm X 25mm

B06 Power Bank

- Battery Capacity: 20,000mAh, 21700
  5,000mAh*4
- Input: USB-C: 5V/3A, 9V/3A, 12V/2.5A,
  15V/2A, 20V/1.5A PD 30W Max
- Output: USB-C: 5V/3A, 9V/3A, 12V/3A,15V/3A,
  20V/3A PD 60W Max
  USB-A: 5V/3A, 9V/2A, 12V/1.5A 18W Max
- Material: Plastic
- Dimensions: 149mm X 58mm X 25mm

C56

- Input: voltage 5V
- Standard: TX module support Apple 5W protocols
- Output power: 5V 4.5W +/-0.5W
- Output Efficiency: 66% at 5V input (TBD)
- Material: Plastic
- Dimension: Ø 34.5mm

C28 126280

- Battery capacity: 126280-10000mAh*1
- Input: USB-C(or Cable): PD 5V/3A, 9V/2.22A, 20W Max
- Output: USBC, USB-Cable,Wireless
  Single USB-C(or Cable):
  PD 5V/3A,9V/2.22A 20W Max
  Wireless: 7.5w Max Qi
  Total 5V/3A 15W Max
- Material: Plastic
- Dimension: 108.65mm X70mm X18.1mm

C28 606072

- Battery capacity: 606072*2-5000mAh*2
- Input: USB-C(or Cable): PD
  5V/3A, 9V/2.22A, 12V/3A, 15V3A, 20V2.25A 45W
- Output: USBC, USB-Cable, Wireless
  Single USB-C(or Cable): PD 5V/3A, 9V/2.22A,
  12V/3A, 15V3A,20V2.25A 45W Max
  Wireless: 25w Max Qi
- Material: Plastic
- Dimension: 108.65mm X70mm X18.1mm

C06 Wireless Charger

- Input: USB-C PD 18W
- Output: Wireless: 5W, 7.5W, 10W
- Material: Plastic and PU
- Dimensions: 90mm X 7.3mm

C30 Magnetic Wireless Car Mount

- Input: USB-C: PD 20W
- Output: Wireless: 5W, 7.5W, 10W
  Total 15W Maximum Output
- Material: Plastic and PU
- Dimensions: 84mm X 64mm X 10mm (Body Only)

C27

- Battery capacity: 506578-5000mAh*1
- nput: USB-C1/C2 PD 5V/3A,9V/2.22A, 20W Max
- Output: USB-C PD 5V/3A,9V/3A,12V/2.5A(30W Max)
  Wireless output: 25w Max
  Total share 5V/3A
- Material: Plastic
- Dimension: 100.8mm X69.8mm X8.3mm

C17

- Input: 5V/9V/12V/15V PD
- Output: 5W, 7.5W, 15W, 25W
- Output: AL and Plastic
- Output: 59mm X7.7mm

C25

- Remark: Magnetic Wireless Charger with PB
- Battery Capacity: 5,000mAh Semi Solid State Battery
  Support MPP 15W
  C25 without stand
  C25L with Stand
- Input: PB mode: USB-C: PD 5V/2A
  Pass-through mode: USB-C PD 20W
- Output: PB mode: USB-C: PD 20W
  Wireless: BPP 5W, Apple 7.5W, MPP 15W
- Case material: Plastic
- Dimension: 105mm X69mm X12.5mm

S43CC- 45W

- Remark: US, JP, EU, UK Plug Available
- Input: AC 100V-240V,50/60Hz, 1A
- Output: Type-C1: 5V/3A, 9V/3A,
  12V/3A, 15V/3A, 20V/2.25A
  Type-C2: 5V/3A, 9V/3A,
  12V/3A, 15V/3A, 20V/2.25A
  Share: Type-C1 PD30W+Type-C2 12W
- Material & Finish: Plastic, Texture
- Dimension: 14.5*43.5*76 mm

S63C - 65W

- Remark: US, JP, EU, UK Plug Available
- Input: AC 100V-240V,50/60Hz, 1.3A
- Output: Type-C1: 5V/3A, 9V/3A, 12V/3A,
  15V/3A, 20V/3.25A
  PPS:5V-20V/3A
- Material & Finish: Plastic, Texture
- Dimension: 34*37.5*64.5 mm(Not include Plug)

S63CA - 65W

- Remark: US, JP, EU, UK Plug Available
- Input: AC 100V-240V,50/60Hz, 1.3A
- Output: Type-C1: 5V/3A, 9V/3A, 12V/3A,
  15V/3A, 20V/3.25A
  USB-A1: 5V/3A, 9V/2A, 12V/2.25A,
  20V1.35A
  Share: Type-C1 PD45W+ USB-A 12W
- Material & Finish: Plastic, Texture
- Dimension: 34*37.5*64.5 mm(Not include Plug)

S63CC - 65W

- Remark: US, JP, EU, UK Plug Available
- Input: AC 100V-240V,50/60Hz, 1.3A
- Output: Type-C1: 5V/3A, 9V/3A, 12V/3A,
  15V/3A, 20V/3.25A
  Type-C2: 5V/3A, 9V/3A, 12V/3A, 15V/3A,
  20V/3.25A
  Share: Type-C1 PD45W+Type-C2 12W
- Material & Finish: Plastic, Texture
- Dimension: 34*37.5*64.5 mm(Not include Plug)

S63CCA - 65W

- Remark: US, JP, EU, UK Plug Available
- Input: AC 100V-240V,50/60Hz, 1.3A
- Output: Type-C1: 5V/3A, 9V/3A, 12V/3A,
  15V/3A, 20V/3.25A
  Type-C2: 5V/3A, 9V/3A, 12V/2.25A, 20V/1.35A
  USB-A: 5V/3A, 9V/3A, 12V/2.25A, 20V/1.35A
  Share: Type-C1 PD45W+(Type-C2+USB-A) 12W
- Material & Finish: Plastic, Texture
- Dimension: 34*37.5*64.5 mm(Not include Plug)

S64CCA - 65W

- Remark: US, JP, EU, UK Plug Available
- Input: AC 100V-240V,50/60Hz, 1.3A
- Output: USB-C1: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A
  USB-C2: 5V/3A, 9V/3A, 12V/2.25A, 20V/1.35A
  USB-A: 5V/3A, 9V/3A, 12V/2.25A, 20V/1.35A
  Share: USB-C1 PD45W + (USB-C2 + USB-A) 12W
- Material & Finish: Plastic, Texture
- Dimension: 34*37.5*71.6 mm(Not include Plug)

T01 - 100W

- Remark: Modified Sine Wave for AC output 110V/220V available Capacity: 27000mAh 6*21700-4500mAh
- Input: USB-C: 5V/3A,9V/3A,12V/3A,15V/3A,20V/3A
- Output: USB-C: 5V/3A,9V/3A,12V/3A,15V/3A,20V/3A
  USB-A: SCP10V/2.25A,5V/3A,9V/2.0A,12V/1.5A
  AC: 220V±3% 50Hz or 110V±3% 60Hz 100W
- Material & Finish: Plastic, Texture
- Dimension: 193*62*85mm/ About 1KG

T02 - 200W

- Remark: Modified Sine Wave for AC output 110V/220V available Capacity: 54000mAh 12*21700-4500mAh
- Input: USB-C: 5V/3A,9V/3A,12V/3A,15V/3A,20V/3A
- Output: USB-C: 5V/3A,9V/3A,12V/3A,15V/3A,20V/3A
  USB-A: SCP10V/2.25A,5V/3A,9V/2.0A,12V/1.5A
  AC: 220V±3% 50Hz or 110V±3% 60Hz 200W
- Material & Finish: Plastic, Texture
- Dimension: 217*83*90mm/ About 1.8KG

S65-CCA 67W

- Input: AC 100V~240V,50/60Hz
- Output: USB-C1: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.35A
  USB-C2: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.35A
  USB-A: 5V/3A, 9V/2A, 12V/1.5A,20V/1.5A
  Share: USB-C1 PD45W+(USB-C2+USB-A) 15W
- Material: Plastic, Texture
- Remark: US, JP, EU, UK Plug Available

S31 - 35W

- Input: AC 100V-240V,50/60Hz
- Output: USB-C: 5V/3A, 9V/3A, 12V/2.9A,
  15V/2.3A, 20V/1.75A
  USB-A: 5V/3A, 9V/3A, 12V/2.5A
  Share: USB-C+USB-A 5V/3A 15W
- Material: Plastic, Texture
- Remark: US, JP, EU, UK Plug Available

S41 - 45W

- Input: AC 100V-240V,50/60Hz
- Output: USB-C1: 5V/3A, 9V/3A, 12V/3A,
  15V/3A, 20V/2.25A
  USB-C2: 5V/3A, 9V/2A,1 2V/3A,
  15V/3A, 20V/2.25A
  Share: USB-C Cable 20W+USB-C2 20W
- Material: Plastic, Texture
- Remark: US, JP, EU, UK Plug Available

S61 - 65W

- Input: AC 100V-240V,50/60Hz
- Output: USB-C1: 5V/3A, 9V/3A, 12V/3A,
  15V/3A, 20V/3.25A
  USB-C2: 5V/3A, 9V/3A, 12V/2.5A,
  15V/2A, 20V/1.5A
  USB-A: 5V/3A, 9V/2A, 12V/2.5A, 20V/1.5A
  Share: USB-C1 PD45W+(USB-C2+USB-A)15W
- Material: Plastic, Texture
- Remark: US, JP, EU, UK Plug Available

S42 - CC 45W

- Input: AC 100V-240V,50/60Hz
- Output: USB-C1: 5V/3A, 9V/3A, 12V/3A,
  15V/3A, 20V/2.25A
  USB-C2: 5V/3A, 9V/2A,1 2V/3A,
  15V/3A, 20V/2.25A
  Share: USB-C1 20W+USB-C2 20W
- Material: Plastic, Texture
- Remark: US, JP, EU, UK Plug Available

S32 - CA 35W

- Input: AC 100V-240V,50/60Hz
- Output: USB-C: 5V/3A, 9V/3A, 12V/2.9A,
  15V/2.3A, 20V/1.75A 35W Max
  USB-A: 5V/3A, 9V/2A, 12V/1.5A
  Share: USB-C+USB-A 5V/3A
- Material: Plastic, Texture
- Remark: US, JP, EU, UK Plug Available

S60 - 65W

- Input: AC 100V-240V,50/60Hz
- Output: USB-C Cable: 5V/3A, 9V/3A,
  12V/3A, 15V/3A, 20V/3.25A
  USB-C2: 5V/3A, 9V/3A, 12V/3A,
  15V/3A, 20V/3.25A
  Share: USB-C Cable 45W+USB-C2 20W
- Material: Plastic, Texture
- Dimension: 60mm X61.85mm X30mm
- Remark: US, JP, EU, UK Plug Available

S62 - CC 65W

- Input: AC 100V-240V,50/60Hz
- Output: USB-C1: 5V/3A, 9V/3A, 12V/3A,
  15V/3A, 20V/3.25A
  USB-C2: 5V/3A, 9V/3A, 12V/3A,
  15V/3A, 20V/3.25A
  Share: USB-C1 45W+USB-C2 20W
- Material: Plastic, Texture
- Remark: US, JP, EU, UK Plug Available

S80

- Input: AC 100V-240V,50/60Hz
- Output: USB-C1: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A
  USB-C2: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A
  USB-C3: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A
  USB-A1: 5V/3A, 9V/2A, 12V/1.5A
  Share: C1+C2+C3+A1: 45W+35W+7.5W+7.5W
  AC Sockets: 10A/110V/1100W
- Material: Plastic, Texture
- Dimension: 93mm X93mm X28.1mm (Not include cable)
- Remark: US, JP, EU, UK Plug Available

S81

- Input: AC 100V-240V,50/60Hz
- Output: USB-C cable: 5V/3A, 9V/3A, 12V/3A,
  15V/3A, 20V/3.25A
  USB-C2: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A
  USB-C3: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A
  USB-A1: 5V/3A, 9V/2A, 12V/1.5A
  Share: C1+C2+C3+A1: 45W+35W+7.5W+7.5W
- Material: Plastic, Texture
- Dimension: 93mm X93mm X28.1mm (Not include cable)
- Remark: US, JP, EU, UK Plug Available

W01

- Input: USB-C: 9V/3A,12V/3A
- Output: Wireless: 5W/7.5W/10W/15W/25W
- Material: Plastic
- Dimension: 64mm X49mm
- Remark: Qi 2.2 25W

W02

- Input: USB-C: 9V/2A
- Output: Wireless: 5W/7.5W/10W/15W
- Material: AL + Glass
- Remark: No Qi Certification
- Dimension: 64.1mm X99mm X25.7mm

W03

- Input: USB-C: 9V/2A
- Outputt: Wireless: 5W/7.5W/10W/15W
- Material: AL + Glass
- Remark: No Qi Certification
- Dimension: 87mm X60mm X6.5mm

S20 - 20W

- Input: AC 100V-240V,50/60Hz
- Output: USB-C: 5V3A,9V2.22A,12V1.67A 20W(Max)
  USB-Cable: 5V3A,9V2.22A,12V1.67A 20W(Max)
  Share: USB-Cable + USB-C 5V/3A 15W(Max)
- Material: Plastic,Texture
- Dimension: 97.5mm X50.9mm X29.8mm
- Remark: US, JP, EU, UK Plug Available

S30 - 30W

- Input: AC 100V-240V,50/60Hz
- Output: USB-C: 5V/3A,9V/3A,12V/2.5A,
  15V/2A,20V/1.5A 30W(Max)
  USB-Cable: 5V/3A, 9V/3A, 12V/2.5A,
  15V/2A, 20V/1.5A 30W(Max)
  Share: USB-Cable + USB-C 5V/3A 15W(Max)
- Material: Plastic, Texture
- Dimension: 61.5mm X50.8mm X30mm
- Remark: US, JP, EU, UK Plug Available

S62F-CCA 65W

- Input: AC 100V-240V,50/60Hz
- Output: USB-C1: 5V/3A,9V/3A,12V/3A,15V/3A,
  20V/3.25A 65W(Max)
  USB-C2: 5V/3A,9V/3A,12V/3A,15V/3A,
  20V/3.25A 65W(Max)
  USB-A: 5V3A,9V2A,12V1.5A 18W(Max)
  Share: USB-C1 45W + (USB-C2+A) 15W 60W(Max)
- Materia & Finish: Plastic,Texture
- Dimension: 50mm X30mm X53.5mm
- Remark: US,JP,EU,UK Plug Available

Y01

- Remark: Battery Capacity: 12000mAh(Lithium polymer battery)
  Start current: 400A-500A
  Peak current: 800A-1000A
  Inflation pressure: 3-140psi
  Inflation flow rate: 22L/min
  Inflation rate: 195/65/R15 tire 0-36psi 5'±5s
- Input: TYPE-C: 5V/3A,9V/3A,12V/2.5A PD 30W
- Output: TYPE-C: 5V/3A,9V/3A,12V/2.5A
  PD 30W USB max 5V/2A
- Material: Plastic
- Dimension: 208mm X92mm X94mm

Y02

(Lithium polymer battery)
- Remark: Battery Capacity: 10000mAh
  Start current: 400A-500A
  Peak current: 800A-1000A
  Inflation pressure: 3-140psi
  Inflation flow rate: 22L/min
  Inflation rate: 195/65/R15 tire 0-36psi 5'±5s
- Input: TYPE-C: 5V/2A,9V/2A
- Output: TYPE-C: 5V/2A
- Material: Plastic
- Dimension: 212mm X107mm X56mm

Y03

(Lithium polymer battery)
- Remark: Battery Capacity: 8000mAh
  Start current: 300A
  Peak current: 500A
- Input: TYPE-C: 5V
- Output: USB: 5V/2A,5V/1A
- Material: Plastic
- Dimension: 187mm X87mm X40mm